

# Edge Mount Trim Tab Kits

## 12-Volt / Single Actuator Kits



### Edge Mount Trim Tab Kits

#### 12-Volt

Designed for boat applications where a lower actuator mounting height is desirable. Actuator mounts at the trailing edge of the blade giving it a 1/2" (1.3 cm) lower mounting height on 9" (22.9 cm) long blades & 3" (7.6 cm) lower mounting height on 12" (30.5 cm) long blades. All edges are turned up for added strength and style. Boat lengths 14' (4.3 m) to 36' (11 m).



15016-101



Blades are constructed of 12 gauge (2.7 mm) laser cut 304 stainless steel with 1" (2.5 cm) turned up edges and a 5 degree taper on both sides to the trailing edge, & 1/8" (3.2 mm) diameter hinge pin. Upper and lower high impact corrosion proof mounting brackets with mechanical cable gland seal.

#### Kits include:


- ▶ (2) 12-gauge stainless steel standard finish blades
- ▶ (2) 15054-001 actuators with 6' (1.8 m) leads and Deutsch connectors
- ▶ (2) 30133-103 actuator extension wiring harnesses - 20' (6.1 m) length
- ▶ (2) 15085-001 upper mounting brackets with gland seal
- ▶ (2) 50014-001 lower mounting brackets
- ▶ Lenco owner's/installation manual
- ▶ Stainless steel mounting hardware



#### SIZE DESCRIPTION

- Ⓛ = Length of tab
- Ⓜ = Width of hinge

Size description to be used with chart below.



#### Edge Mount

#### Retail Box

See check-list below



### Electro-Polished Edge Mount Trim Tab Kits

#### 12-Volt

All the same features of the Edge Mount series with the addition of Electro-Polished blades. Electro-Polish adds a mirror finish and the ultimate corrosion protection. Actuator mounts at the trailing edge of these 12" (30.5 cm) blades giving them a 3" (7.6 cm) lower mounting height. Boat Lengths 14' (4.3 m) to 30' (9.1 m).



15116-101



Blades are constructed of Electro-Polished 12 gauge (2.7 mm) laser cut 304 stainless steel with a 1" (2.5 cm) turned up edges and a 5 degree taper on both sides to the trailing edge & 1/8" (3.2 mm) diameter hinge pin. Upper and lower high impact corrosion proof mounting brackets with mechanical cable gland seal.

#### Kits include:


- ▶ (2) 12-gauge stainless steel Electro-Polished blades
- ▶ (2) 15054-001 actuators with 6' (1.8 m) leads and Deutsch connectors
- ▶ (2) 30133-103 actuator extension wiring harnesses - 20' (6.1 m) length
- ▶ (2) 15085-001 upper mounting brackets with gland seal
- ▶ (2) 50014-001 lower mounting brackets
- ▶ Lenco owner's/installation manual
- ▶ Stainless steel mounting hardware



#### SIZE DESCRIPTION

- Ⓛ = Length of tab
- Ⓜ = Width of hinge

Size description to be used with chart below.



#### Edge Mount

#### Retail Box

See check-list below



#### Edge Mount Trim Tab Kits - 12-volt

Lenco Part#	L" X W"	Boat Length	Hinge Height	Min.Transom Height	Retail Box
15013-101	9" X 9"	14' - 18'	2" (5.1 cm)	13.5" (34.3 cm)	✓
15014-101	9" X 12"	16' - 25'	2" (5.1 cm)	13.5" (34.3 cm)	✓
15015-101	12" X 9"	14' - 18'	2" (5.1 cm)	11" (27.9 cm)	✓
15016-101	12" X 12"	17' - 30'	2" (5.1 cm)	11" (27.9 cm)	✓
15017-101	12" X 18"	26' - 36'	2" (5.1 cm)	11" (27.9 cm)	✓

#### Edge Mount Electro-Polished Trim Tab Kits - 12-Volt

Lenco Part#	L" X W"	Boat Length	Hinge Height	Min Transom Height	Retail Box
15115-101	12" X 9"	14' - 18'	2" (5.1 cm)	11" (27.9 cm)	✓
15116-101	12" X 12"	17' - 30'	2" (5.1 cm)	11" (27.9 cm)	✓

#### SWITCH KITS SOLD SEPARATELY

See page 20 through 21.

#### SWITCH KITS SOLD SEPARATELY

See Lenco catalog page 20 through 21 or visit the product section of [lencmarine.com](http://lencmarine.com)

WE MAKE THE BEST BOATS BETTER!